

Πληροφορίες-Χαρακτηριστικά



ΣΥΣΤΟΛΗ ΡΕ Ε/Α ΟΜΟΚΕΝΤΡΗ ΚΟΝΤΗ

HDPE 100

ΚΑΤΑ EN 12201-3

ΧΡΩΜΑ: ΜΑΥΡΟ

Ø	PN10	PN16
25/20	-	✓
32/20	-	✓
32/25	-	✓
40/20	✓	✓
40/25	✓	✓
40/32	✓	✓
50/25	✓	✓
50/32	✓	✓
50/40	✓	✓
63/32	✓	✓
63/40	✓	✓
63/50	✓	✓
75/32	✓	✓
75/40	✓	✓
75/50	✓	✓
75/63	✓	✓
90/50	✓	✓
90/63	✓	✓
90/75	✓	✓
110/50	✓	✓
110/63	✓	✓
110/75	✓	✓
110/90	✓	✓
125/63	✓	✓
125/75	✓	✓
125/90	✓	✓
125/110	✓	✓
140/75	✓	✓
140/90	✓	✓
140/110	✓	✓
140/125	✓	✓
160/90	✓	✓
160/110	✓	✓
160/125	✓	✓

Ø	PN5	PN10	PN16
160/140	-	✓	✓
180/90	-	✓	✓
180/110	-	✓	✓
180/125	-	✓	✓
180/140	-	✓	✓
180/160	-	✓	✓
200/140	✓	✓	✓
200/160	✓	✓	✓
200/180	✓	✓	✓
225/140	-	✓	✓
225/160	✓	✓	✓
225/180	✓	✓	✓
225/200	✓	✓	✓
250/160	✓	✓	✓
250/180	✓	✓	✓
250/200	✓	✓	✓
250/225	✓	✓	✓
280/200	✓	✓	✓
280/225	✓	✓	✓
280/250	✓	✓	✓
315/200	✓	✓	✓
315/225	✓	✓	✓
315/250	✓	✓	✓
315/280	✓	✓	✓
355/250	✓	✓	✓
355/280	✓	✓	✓
355/315	✓	✓	✓
400/280	✓	✓	✓
400/315	✓	✓	✓
400/355	✓	✓	✓
450/315	✓	✓	✓
450/355	✓	✓	✓
450/400	✓	✓	✓
500/355	✓	✓	✓

Ø	PN5	PN10	PN16
500/400	✓	✓	✓
500/450	✓	✓	✓
560/400	✓	✓	✓
560/450	✓	✓	✓
560/500	✓	✓	✓
630/450	✓	✓	✓
630/500	✓	✓	✓
630/560	✓	✓	✓
710/560	✓	✓	-
710/630	✓	✓	-
800/710	✓	✓	-
900/800	✓	✓	-
1000/900	✓	✓	-