



Πληροφορίες-Χαρακτηριστικά

ΤΑΥ ΡΕ Ε/Α ΣΥΣΤΟΛΙΚΑ ΕΝΙΣΧΥΜΕΝΑ

HDPE 100

ΚΑΤΑ EN 12201-3

ΧΡΩΜΑ: ΜΑΥΡΟ

Ø	PN10	PN16
200/75	✓	✓
200/140	✓	✓
225/63	✓	✓
225/125	✓	✓
225/140	✓	✓
250/63	✓	✓
250/75	✓	✓
250/90	✓	✓
250/110	✓	✓
250/125	✓	✓
250/160	✓	✓
250/180	✓	✓
250/200	✓	✓
280/63	✓	✓
280/75	✓	✓
280/90	✓	✓
280/110	✓	✓
280/125	✓	✓
280/140	✓	✓
280/160	✓	✓
280/180	✓	✓
280/200	✓	✓
315/63	✓	✓
315/75	✓	✓
315/125	✓	✓
315/140	✓	✓
315/180	✓	✓
355/63	✓	✓
355/75	✓	✓
355/90	✓	✓
355/110	✓	✓
355/125	✓	✓
355/140	✓	✓
355/160	✓	✓

Ø	PN10	PN16
355/180	✓	✓
355/200	✓	✓
355/225	✓	✓
355/250	✓	✓
400/63	✓	✓
400/75	✓	✓
400/90	✓	✓
400/110	✓	✓
400/125	✓	✓
400/140	✓	✓
400/160	✓	✓
400/180	✓	✓
400/200	✓	✓
400/225	✓	✓
400/250	✓	✓
450/63	✓	✓
450/75	✓	✓
450/90	✓	✓
450/110	✓	✓
450/125	✓	✓
450/160	✓	✓
450/200	✓	✓
450/225	✓	✓
450/250	✓	✓
500/63	✓	✓
500/75	✓	✓
500/90	✓	✓
500/110	✓	✓
500/125	✓	✓
500/140	✓	✓
500/160	✓	✓
500/180	✓	✓
500/200	✓	✓
500/225	✓	✓
500/250	✓	✓