



## Πληροφορίες-Χαρακτηριστικά

| Ø       | PN10 | PN16 | PN25 |
|---------|------|------|------|
| 63/50   | ✓    | ✓    | ✓    |
| 75/32   | -    | ✓    | ✓    |
| 75/40   | -    | -    | ✓    |
| 75/50   | ✓    | ✓    | ✓    |
| 75/63   | ✓    | ✓    | ✓    |
| 90/50   | ✓    | ✓    | ✓    |
| 90/63   | ✓    | ✓    | ✓    |
| 90/75   | ✓    | ✓    | ✓    |
| 110/50  | ✓    | ✓    | -    |
| 110/63  | ✓    | ✓    | ✓    |
| 110/75  | ✓    | ✓    | ✓    |
| 110/90  | ✓    | ✓    | ✓    |
| 125/63  | ✓    | ✓    | ✓    |
| 125/75  | -    | ✓    | ✓    |
| 125/90  | ✓    | ✓    | ✓    |
| 125/110 | ✓    | ✓    | ✓    |
| 140/63  | ✓    | ✓    | ✓    |
| 140/75  | ✓    | ✓    | ✓    |
| 140/90  | ✓    | ✓    | ✓    |
| 140/110 | ✓    | ✓    | ✓    |
| 160/63  | ✓    | ✓    | ✓    |
| 160/75  | ✓    | ✓    | ✓    |
| 160/90  | ✓    | ✓    | ✓    |
| 160/110 | ✓    | ✓    | ✓    |
| 160/125 | ✓    | ✓    | ✓    |
| 180/63  | ✓    | ✓    | -    |
| 180/90  | ✓    | ✓    | -    |
| 180/110 | -    | ✓    | -    |
| 180/125 | -    | ✓    | -    |
| 180/160 | ✓    | ✓    | -    |

## ΤΑΥ ΣΥΣΤΟΛΙΚΟ Ε/Α ΜΑΚΡΥ

## INJECTION

HDPE 100

ΚΑΤΑ EN 12201-3

ΧΡΩΜΑ: ΜΑΥΡΟ

| Ø       | PN10 | PN16 | PN25 |
|---------|------|------|------|
| 200/63  | ✓    | ✓    | -    |
| 200/90  | ✓    | ✓    | -    |
| 200/110 | ✓    | ✓    | -    |
| 200/125 | ✓    | ✓    | -    |
| 200/160 | ✓    | ✓    | -    |
| 225/75  | ✓    | ✓    | -    |
| 225/90  | ✓    | ✓    | -    |
| 225/110 | ✓    | ✓    | -    |
| 225/160 | ✓    | ✓    | -    |
| 225/180 | ✓    | ✓    | -    |
| 250/110 | ✓    | ✓    | -    |
| 250/160 | ✓    | ✓    | -    |
| 250/180 | -    | ✓    | -    |
| 250/200 | ✓    | ✓    | -    |
| 315/90  | ✓    | ✓    | -    |
| 315/110 | ✓    | ✓    | -    |
| 315/160 | ✓    | ✓    | -    |
| 315/200 | ✓    | ✓    | -    |
| 315/225 | ✓    | ✓    | -    |
| 315/250 | ✓    | ✓    | -    |